

Penetrating Sealer

PRODUCT DESCRIPTION

Jesmonite Penetrating Sealer is designed for use with all Jesmonite cementitious materials. These include AC630, AC730, AC830, AC930 & Flex Metal Surfaces.

Penetrating Sealer provides invisible protection by way of impregnating the surface, offering repellence of water and oil while providing good stain resistance against many liquids and general environmental contamination.

Penetrating Sealer should be utilised where stain resistance is a priority, and the natural surface finish needs to remain unchanged.

APPLICATION AREAS

We recommend that Penetrating Sealer is applied in two coats, with the second coat being applied once the first coat has become touch-dry. Do not allow the first coat to dry completely before applying the second coat. Penetrating Sealer can be applied using a high-quality brush or sprayed onto the surface. Ensure that all surfaces are clean, dry, and free from any contamination prior to application.

KEY ATTRIBUTES

- The existing surface quality is preserved, becoming highly water and oil repellent.
- Contaminants are unable to adhere to the surface.
- Cleaning becomes much easier and less frequent.
- The lifespan of the substrate is extended because of reduced cleaning cycles.
- The surface remains clean and will not discolour.

PACKAGING

Products are supplied in a variety of sizes dependant on location, therefore please check your local 'Official Reseller' for accurate formats or visit www.jesmonite.com for further information on Official Packaging.

FOOD SAFETY

Jesmonite materials have not been tested for food safety.

STORAGE

For maximum efficacy products should be stored at a constant temperature of between 5 – 25°C. Keep clean, dry and away from any contaminants. Freezing must be avoided.

TECHNICAL DATA SHEET

Reference: TDS-PS-25-EW

JESMONITE[®]
MADE FROM

Jesmonite[®] is a Registered Trademark

The above information and recommendations are based upon our experience and are offered merely for advice. They are offered in good faith but without guarantee, as conditions and methods of use are beyond our control. It remains the responsibility of the end user to determine the suitability of the materials for the particular purpose intended.