

# Super Plasticiser

## PRODUCT DESCRIPTION

Jesmonite Super Plasticiser is a high-performance additive designed to enhance the workability and versatility of Jesmonite cementitious composites. This specialised product improves the fluidity of your mixture without the need to add extra water, allowing for intricate detailing and complex casting with ease.

## SPECIFICATIONS

Addition rate	8g- 12g (per kg of mix)
Product compatibility	AC630
	AC730
	AC830
	AC930
	AC84

## APPLICATION AREAS

Cast and laminated mouldings alongside spray applications. Simply add the recommended amount of Super Plasticiser to your mix during the blending process for optimal results.

## KEY ATTRIBUTES

- Enhanced workability
- Improved overall strength
- Efficient mixing

## PACKAGING

Products are supplied in a variety of sizes dependant on location, therefore please check your local 'Official Reseller' for accurate formats or visit [www.jesmonite.com](http://www.jesmonite.com) for further information on Official Packaging.

## FOOD SAFETY

Jesmonite materials have not been tested for food safety.

## STORAGE

For maximum efficacy products should be stored at a constant temperature of between 5 – 25°C. Keep clean, dry and away from any contaminants, powders should be kept in sealed containers. Freezing must be avoided.

## DOSING WARNING

Do not overdose your mix with Super Plasticiser, as over plasticising may have an adverse effect on your finished piece – over plasticising can cause mix segregation, resulting in splitting, cracking and unstable finished products.

Jesmonite<sup>®</sup> is a Registered Trademark

*The above information and recommendations are based upon our experience and are offered merely for advice. They are offered in good faith but without guarantee, as conditions and methods of use are beyond our control. It remains the responsibility of the end user to determine the suitability of the materials for the particular purpose intended.*